

SPECIFICATIONS OD-580T & OD-580W

OD-580T & OD-580W

ENGINE

Engine Type	Water cooled 4 cycle Diesel engine 3-cyl; EPA Tier 4
Model Name	KUBOTA D1703-M
Total Displacement	100.5 cu.in.
Engine Power - SAE J1995 Gross	25 hp
Rated Speed	2,200 rpm
Low Idling Speed	1,100 rpm

DIMENSIONS

Overall Length (w/o Bucket)	87.4 in (2220 mm)
Overall Height	62.4 in (1585 mm)
Overall Width	42 in (1067 mm)
Wheelbase	42.7 in (1085 mm)
Hinge Pin Height at Max. Lift	82.6 in (2098 mm)
Operating Weight	2970 lb (1347 kg)
Tipping Load	2857 lb (1296 kg)
Rated Operating Capacity (35%)	1000 lb (454 kg)
Track Width	7.8 in (198 mm)
Ground Clearance	3.7 in (94 mm)
Angle of Departure	27°

PERFORMANCE

Attachment Mounting System	CII (Common Industry Interface)
Travel Speed (Fwd/Rev)	4.94 mph (7.95 km/h)
Battery Capacity	12V, 60Ah
Auxiliary Hydraulic Flow	12.68 gal/min (48 L/min)

SERVICE AND FILL CAPACITIES

Fuel Tank Capacity	9.25 gal (35 L)
Hydraulic System	9.25 gal (35 L)